



**Industrial  
Oleochemical  
Products**

# PRODUCT DATA SHEET

317 Chamberlain Road, Jacobs, South Africa, 4026  
Tel: +27 (0) 31 461 8680 Fax : +27 (0) 31 461 3743  
Website: www.oleo.co.za Email: info@oleo.co.za

## OleoRez RG75 L

### Glycerol ester of tall oil rosin

OleoRez RG 75 L is a light-coloured glycerol ester of tall oil rosin which exhibits a softening point of nominally 75°C. OleoRez RG 75 L tackifier has been stabilized to provide excellent tack performance and aging stability. It makes it a very useful tackifier for wide variety of adhesives, more especially pressure sensitive adhesives.

### Physical Properties

Property	Description
Appearance @25 °C	Clear light yellow (<=20mm) nuggets
Solids	100%
Acid value (mgKOH/g)	12 - 20
Softening Point , (°C)	73 - 76
Colour, (Gardner)	3 - 5

### Applications

Premium hot melt packaging adhesives	Sealants
Pressure sensitive adhesives	Coatings

### Personal Protective Equipment



Always handle OleoRez product in accordance with the safety data sheet (SDS) and proper safety procedures.

### Useful Product Information

CAS Number	8050-31-5
EC Number	232-482-5
HS Code	3806.30.00
Flash Point , (°C)	>230
Specific gravity, 25/25°C	Approx. 1.05
Solubility	Fully soluble in aromatics, esters and ketones, partially soluble in white spirit and insoluble in alcohols and water.
Compatibility	Compatible with most commonly used EVAs, paraffin and waxes, natural rubber, SIS, and SBS



OleoRez RG 75 L

# PRODUCT DATA SHEET

317 Chamberlain Road, Jacobs, South Africa, 4026  
Tel: +27 (0) 31 461 8680 Fax : +27 (0) 31 461 3743  
Website: www.oleo.co.za Email: info@oleo.co.za

## Feature & Benefits

Excellent colour stability	Low volatility at elevated temperatures
Improved flexibility in formulating	High tackifying properties
Minimal odour	Good ageing stability
Broad compatibility	Good adhesion to a variety of substrates
Formulated with an antioxidant to provide oxidative stability	Minimal colour shift at elevated temperatures



## Product Packaging

Pallet: 25kgs x 40 and plastic shrink wrapped  
Possibility of 1 ton bulk bags

## Other Adhesive Tackifiers

**OleoRez RP105, RG100L, RG70-L, RPG90-L, RPG100L**



Handling:	Ensure the use of personal protective equipment (see SDS Section 8) Handle and open container with care. Keep away from heat and sources of ignition. The material is combustible but not classified as flammable. Wash thoroughly after handling. Do not eat and drink or smoke while handling this material. For molten rosin ester (>100°C) wear protective apron, footwear, spats, face mask and thermally protective gloves For rosin ester dust, wear a protective mask and gloves Note that handling of rosin ester in solid form may constitute a dust hazard (see SDS: Section 5)
Storage:	Store in original packaging and keep containers tightly closed until ready for use. Store in a cool, dry, well-ventilated place.
Incompatible materials:	Rosin ester in contact with un-lined mild steel containers or pipes can result in darkening of the material

### Disclaimer

The data contained herein is believed to be accurate. However, neither the above named supplier nor of its partners or distributors assumes any legal liability whatsoever for the accuracy or completeness of information contained herein. Users should undertake sufficient verification and testing to determine the suitability for their own purpose of any product or information contained herein.