



Industrial  
Oleochemical  
Products

# SAFETY DATA SHEET

317 Chamberlain Road, Jacobs, South Africa, 4026  
Tel: +27 (0) 31 461 8680 Fax : +27 (0) 31 461 3743  
Website: [www.oleo.co.za](http://www.oleo.co.za) Email: [info@oleo.co.za](mailto:info@oleo.co.za)

## OleoPrint 155MT

### Modified Polyol ester of tall oil rosin

OleoPrint 155MT is a modified polyol ester of naturally renewable tall oil rosin designed specifically for a variety printing ink applications. It is formulated to provide nitrocellulose compatibility and is used in formulating printing inks that contain toluene.

#### 1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER:

<b>Product name:</b>	OleoPrint 155MT	
<b>Product identifier/synonyms:</b>	Ester of tall oil rosin, modified	CAS # 68333-69-7 EC # 614-421-8
<b>Product description:</b>	Ester of modified rosin acids	
<b>Intended use:</b>	Printing Inks	
<b>Application of the substance / the mixture</b>	Letterpress, offset, and gravure-type printing inks Varnishes that require faster bodying, higher viscosities, and faster film drying Toners for printers and copiers	
<b>Manufacturer:</b>	Industrial Oleochemical Products, (Pty) Ltd., Jacobs, 4052, KZN, Tel: +27-(0)31-4618680, Fax: +27-(0)31-461-3743 <a href="mailto:info@oleo.co.za">info@oleo.co.za</a>	
<b>Emergency telephone number:</b>	031-461-8721 (Monday-Friday 08.00 to 16.30hr) 031-461-8680 (after normal working hours) 071-483-7688 (medical emergencies)	



OleoPrint 155MT

#### 2. HAZARD IDENTIFICATION

This substance is not classified according to South African National Standard SANS 10234:2007, Globally Harmonized System of classification and labelling of chemicals (GHS). This substance is not classified in the Annex I of Directive 67/548/ (Index # 650-015-00-7) according to ESIS (European Chemical Substances Information System).

##### Flammability:

Hazard category	Criteria
0	Flash point (COC) >230°C

(continues on page 2)

# SAFETY DATA SHEET

## OleoPrint 155MT Modified Polyol ester of tall oil rosin

### HAZARD IDENTIFICATION: (continuation from page 1)

**Classification of the substance or mixture**



GHS07

Skin Sensitisation 1B  
H317 May cause an allergic skin reaction

Eye Irritation 2B:  
H320 Causes eye irritation

May form combustible dust concentration in air

### Classification according to Directive 67/548/EEC or Directive 1999/45/EC

**Information concerning particular hazards for human and environment**

#### WARNING!

Static charges generated by emptying package in or near flammable vapours may cause flash fire. May form flammable dust-air mixtures.

#### POTENTIAL HEALTH EFFECTS – (Solid product at ambient temperatures)

May cause eye irritation by mechanical abrasion. May cause skin irritation by mechanical abrasion. Inhalation may cause respiratory tract irritation.

Prolonged or repeated contact may cause skin irritation and may cause skin sensitisation (allergic reaction) in susceptible individuals.

Prolonged exposure to smoke or fumes generated by heating this product may cause respiratory irritation with throat discomfort, coughing, or breathing difficulty. Repeated exposure may lead to respiratory sensitisation (asthma) in susceptible individuals.

#### GENERAL HYGIENIC PRACTICES

Avoid contact with eyes, skin, and clothing. Avoid breathing dust, vapours or mist. Handle in areas with adequate ventilation.

Refer to SDS Section 8, Exposure Controls / Personal Protection, for further information.

Refer to Section 5 for Hazardous Combustion Products, and Section 10 for Hazardous Decomposition / Hazardous Polymerization Products

#### Label elements (GHS label elements)

**The substance is classified and labelled according to the Global Harmonized System (GHS)**

#### Hazard pictograms



GHS07

#### Signal word

Warning

#### Hazard statements

H320 Causes eye irritation  
H317 May cause an allergic skin reaction  
May form combustible dust concentrations in air

(continues on page 3)

# SAFETY DATA SHEET

## OleoPrint 155MT Modified Polyol ester of tall oil rosin

### HAZARD IDENTIFICATION: (Continuation from page 2)


#### PRECAUTIONARY STATEMENTS

<b>P202</b>	Do not handle until all safety precautions have been read and understood
<b>P210</b>	Keep away from heat / sparks / open flames / hot surfaces – NO SMOKING
<b>P234</b>	Keep only in original packaging
<b>P243</b>	Take precautionary measures against static discharge
<b>P261</b>	Avoid breathing dust / fume/ gas/mist / vapours/ spray
<b>P262</b>	Do not get in eyes, on skin, or on clothing
<b>P264</b>	Wash thoroughly after handling
<b>P270</b>	Do not eat, drink or smoke when using this product
<b>P280</b>	Wear protective gloves / eye protection
<b>P284</b>	In case of inadequate ventilation wear respiratory protection
<b>P 301 + P312</b>	If swallowed: call a doctor if you feel unwell
<b>P301 + P330 + P331</b>	If swallowed: Rinse mouth. DO NOT induce vomiting
<b>P302 + P352</b>	If on skin: Wash with plenty of soap and water
<b>P304 + P312</b>	IF INHALED: Call a doctor if you feel unwell
<b>P304 + P341</b>	If inhaled: if breathing is difficult, remove person to fresh air and keep comfortable for breathing
<b>P305 + P351 + P338</b>	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do, continue rinsing.

#### PRECAUTIONARY STATEMENTS

P314	Get medical advice / attention if you feel unwell
P333 + P313	If skin irritation or rash occurs: get medical advice / attention
P363	Wash contaminated clothing before reuse
P402 + P404	Store in a dry place. Store in a closed packaging
P403 + P233	Store in a well ventilated place. Keep packaging tightly closed
P501	Dispose of contents / packaging in accordance with local / regional / national/ international regulations

#### CLASSIFICATION SYSTEM : NFPA RATINGS (scale 0- 4)



HEALTH = 0

FIRE = 1

REACTIVITY = 0

#### HMIS RATINGS (scale 0 – 4)

HEALTH	0
FIRE	1
REACTIVITY	0

HEALTH = 0

FIRE = 1

REACTIVITY = 0

#### Other Hazards

Results of PBT and vPvB assessment

#### PBT

Not applicable

#### vPvB

Not applicable

(continues on page 4)

# SAFETY DATA SHEET

## OleoPrint 155MT Modified Polyol ester of tall oil rosin

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

#### CHEMICAL CHARACTERISATION: SUBSTANCE

<b>CAS number</b>	68333-69-7
<b>CAS number description</b>	Maleated, polymer with pentaerythritol
<b>EC number</b>	614-421-8
<b>Additional information</b>	<p>This product is considered hazardous according to the OSHA Hazard Communication Standard 29CFR1910.1200 due to flammable dust potential.</p> <p>If the product is heated or used at temperatures sufficient to produce smoke or fumes, refer to SDS Section 8, Recommended Exposure Limits and Personal Protective Equipment.</p>

### 4. FIRST-AID MEASURES

#### DESCRIPTION OF FIRST AID MEASURES

<b>After inhalation</b>	Remove to fresh air. Get medical attention if nasal, throat or lung irritation develops
<b>After skin contact</b>	<b>HOT MOLTEN product:</b> immediately cool skin burns with water and cold packs for at least 15 minutes.

#### DESCRIPTION OF FIRST AID MEASURES

<b>After skin contact</b>	<p>DO NOT put ice directly on the skin. DO NOT attempt to remove solidified resin from the skin as severe tissue damage may result. Get immediate medical attention. See Note to Medical Doctor below.</p> <p><b>SOLID product at ambient temperatures :</b> Wash thoroughly with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists. Thoroughly wash clothing before reuse. See Note to Medical Doctor below.</p>
<b>After eye contact</b>	<p><b>HOT MOLTEN product:</b> Cool burns with plenty of low pressure water. Get immediate medical attention.</p> <p><b>SOLID product at ambient temperature:</b> Remove contact lenses. Hold eyelids apart. Immediately flush eyes with plenty of low pressure water for at least 15 minutes. Get medical attention if irritation persists.</p>
<b>After swallowing</b>	<p>Not an ingestion hazard under anticipated conditions of use.</p> <p><b>For accidental ingestion:</b> DO NOT induce vomiting. Get immediate medical attention.</p>
	(continues on page 5)

# SAFETY DATA SHEET

## OleoPrint 155MT Modified Polyol ester of tall oil rosin

### 4. FIRST-AID MEASURES (continues from page 4)

#### INFORMATION FOR MEDICAL DOCTOR

<b>For MOLTEN or HOT LIQUID product</b>	Material should not be forcibly removed from the skin. Mineral oil maybe used to loosen and soften the material This product contains rosin or a rosin derivative. Rosin and some of its derivatives have been reported to cause an allergic skin reaction (sensitisation) in susceptible individuals after repeated or prolonged skin contact. Smoke or fumes generated by heating product may lead to respiratory sensitisation (asthma) in susceptible individuals.
<b>Most important symptoms and effects, both acute and delayed</b>	No further relevant information available
<b>Indication of any immediate medical attention and special treatment needed</b>	No further relevant information available.

### 5. FIRE FIGHTING MEASURES

#### Extinguishing media

<b>Suitable extinguishing agents</b>	Water spray, dry chemical, foam, carbon dioxide or clean extinguishing agents may be used on fires involving this product
<b>Special hazards arising from the substance or mixture</b>	If heated to combustion, the following substances may be formed: Carbon monoxide (CO); Carbon Dioxide (CO <sub>2</sub> ); Aldehydes, Carboxylic acids; Smoke

#### Advise for fire-fighters

<b>Protective equipment</b>	Wear self-contained breathing apparatus pressure-demand. MSHA/NIOSH approved (or equivalent) and full protective gear when fighting fires involving this product.  Apply water to <b>HOT MOLTEN or HOT LIQUID</b> resin fires from a safe, protected location to avoid body contact with hot rosin.  Cool packaging with water to prevent rupture.
-----------------------------	--

### 6. ACCIDENTAL RELEASE MEASURES

<b>Personal precautions, protective equipment and emergency procedures</b>	<b>For HOT MOLTEN or HOT LIQUID product:</b> Wear protective equipment as required (see SDS Section 8). Contain spilled material and allow it to cool and solidify. DO NOT apply water. After solidification, clean up and place in suitable containers for use or disposal.  <b>For SOLID product:</b> Ventilate area. Avoid dust formation. If product is not contaminated, scoop into clean containers for use. If product is contaminated scoop into containers, and dispose appropriately. In case of accidental spills or release, refer to Section 8, Personal Protective Equipment and General Hygiene Practices.  (continues on page 6)
--	--

# SAFETY DATA SHEET

## OleoPrint 155MT Modified Polyol ester of tall oil rosin

### 6. ACCIDENTAL RELEASE MEASURES (cont...from page 5)

<b>Environmental precautions</b>	No special measured required
<b>Methods and material for containment and cleaning up</b>	Pick up mechanically
<b>Reference to other sections</b>	See Section 7 for information on safe handling See Section 8 for information on personal protective equipment See Section 13 for disposal information

### 7. HANDLING AND STORAGE

<b>Precautions for safe handling</b>	For <b>HOT MOLTEN or HOT LIQUID product</b> : Use personal protective equipment as indicated in Section 8: Exposure Controls / Personal Protection  For <b>SOLID product</b> : Earth all equipment. Blanket vessel with inert gas when emptying bags where flammable vapours may be present. Earth operator and pour material slowly into conductive, earth chute.
<b>Information about protection against explosions and fires</b>	Water contact with HOT MOLTEN or HOT LIQUID resin may result in foaming or spattering, which can cause eye or skin burns. Avoid conditions that generate dust; product may form flammable dust-air mixtures. Avoid emptying package in or near flammable vapours; charges may cause flash fire. Keep away from heat, flame, sparks and other ignition sources.

### Conditions for safe storage, including any incompatibilities

<b>Requirements to be met by storerooms and receptacles</b>	Store at ambient temperature Keep bags closed when not in use
<b>Information about storage in one common storage facility</b>	Not required
<b>Further information about storage conditions</b>	Dry well ventilated
<b>Specific end use(s)</b>	No further information available

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<b>Additional information about design of technical systems</b>	Eyewash fountains and safety showers should be easily accessible. If user operations generate dust or fumes: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Discharge from the ventilation system should comply with applicable air pollution control regulations. Eliminate ignition sources and prevent build up of static electrical charges. Completely isolate and thoroughly clean all equipment, piping, or vessels before beginning maintenance or repairs. Keep area clean. Product will burn
<b>Control parameters</b>	
<b>Components with limit values that require monitoring at the workplace</b>	Not required  (continues on page 7)

# SAFETY DATA SHEET

## OleoPrint 155MT Modified Polyol ester of tall oil rosin

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

(continues from page 6)

#### Control parameters

#### Additional Occupational Exposure Limit Values for possible hazard during processing

This product may present an inhalation health hazard if used under conditions that could generate dust or fumes.

PARTICULATES (INSOLUBLE) NOT OTHERWISE SPECIFIED (PNOS): If used under conditions that generate particulates, the ACGIH TLV-TWA of 3 mg/m<sup>3</sup> respirable fraction (10 mg/m<sup>3</sup> total) should be observed.

ROSIN PYROLYSIS FUMES: If the product is heated to temperatures sufficient to produce smoke or fumes, maintain exposure to resin acids to be lowest achievable concentration using recommended engineering controls and personal protective equipment.

#### Exposure controls – Personal Protective equipment

#### General protective and hygiene measures

Avoid contact with eyes, skin and clothing  
 Avoid breathing dust or fumes  
 Handle in areas with adequate ventilation.  
 Avoid contamination of food, beverages, or smoking materials.  
 Wash thoroughly after handling and before eating, drinking or smoking.  
 Remove contaminated clothing promptly and clean thoroughly before reuse.

#### Breathing equipment

Appropriate respiratory protection is required when exposure to airborne contaminants may exceed acceptable limits. Respirators should be selected and used in accordance with OSHA, subpart 1 (29 CFR 1910.134) and manufacturer's recommendations

#### Protection of hands

Impervious gloves  
 The glove material has to be impermeable and resistant to the product / the substance / the preparation.  
 Selection of the glove material should be based on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### Eye protection

Safety glasses

#### Body protection

Appropriate protective clothing  
 Personnel exposed to HOT MOLTEN or HOT LIQUID material should wear protective clothing that provides protection against thermal burns.

(continues on page 8)

# SAFETY DATA SHEET

## OleoPrint 155MT Modified Polyol ester of tall oil rosin

<b>Body protection</b> (continuation from page 7)	Required Protective Equipment: 1, Long-sleeved protective shirt, long pants and work shoes; 2, Hard hat and face shield; 3, Long-cuff gloves extending beyond wrist; 4, Lined rain suit with protective hood or shoulder shroud or 5, Full aluminized or thermal suit with hood.
--	---



### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties :

##### General information

<b>Appearance Form</b>	solid at ambient temperatures
<b>Appearance colour</b>	yellow to light amber
<b>Odour</b>	typical rosin
<b>Percent Volatile</b>	Negligible at 25(°C)
<b>Specific gravity</b>	1.11 g/ml
<b>Vapour density</b>	Heavier than air
<b>Change in condition Softening point</b>	145 - 155 (°C) (Ring & Ball)
<b>Flash Point</b>	> 230 (°C) (Closed cup)
<b>Danger of explosion</b>	Product is not explosive, However, formation of explosive air/dust mixtures are possible <b>15g/M<sup>3</sup> of resin dust can ignite explosively.</b>
<b>Vapour pressure at 20 (°C)</b>	Negligible hPa
<b>Density</b>	1.05 kg/m <sup>3</sup>
<b>Solubility in / Miscibility with water</b>	Negligible
<b>Other information</b>	No further relevant information available

### 10. STABILITY AND REACTIVITY

#### Reactivity and Chemical Stability

<b>Thermal decomposition / conditions to be avoided</b>	Stable under recommended handling and storage conditions
<b>Possibility of hazardous reactions</b>	No dangerous reactions known
<b>Conditions to avoid</b>	<b>Excessive heating</b> <b>Dust /Air mixtures can ignite explosively</b>
<b>Incompatible materials</b>	None known
<b>Hazardous decomposition products</b>	No dangerous decomposition products known

### 11. TOXICOLOGICAL INFORMATION

#### Information on toxicological effects

##### Acute toxicity

##### LD/LC50 values that are relevant for classification

<b>Oral LD50</b>	SIMILAR PRODUCTS: Not toxic by OSHA/ANSI criteria based on acute animal peroral testing of this or similar product (LD50 >5000 mg/kg). Feeding studies of this or similar products indicate no evidence of risk at anticipated workplace exposure levels. Mild reversible respiratory irritation from single and repeated inhalation exposure to heated vapours of this or a similar product.
<b>Primary irritant effect on the skin</b>	Mild skin irritant
<b>Primary irritant effect on the eye</b>	The fine particles and powder should be regarded as an inert, nuisance dust
	(continues on page 9)



# SAFETY DATA SHEET

## OleoPrint 155MT Modified Polyol ester of tall oil rosin

### 11. TOXICOLOGICAL INFORMATION

(continuation from page 8)

<b>Sensitisation</b>	Due to the physical nature of this material, may cause eye, skin and respiratory irritation by mechanical abrasion. This product contains rosin or a rosin derivative. Rosin and some rosin derivatives have been reported to cause allergic skin reaction ( sensitisation) in susceptible individuals after repeated or prolonged contact. Smoke or fumes generated by heating may lead to respiratory sensitisation (asthma) in susceptible individuals
<b>Additional toxicological information</b> IARC (International Agency for Research on Cancer: Substance is not listed	Carcinogenic categories  Substance is not listed
<b>NTP (National Toxicology Program)</b>	Substance is not listed
<b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>	Substance is not listed

### 12. ECOLOGICAL INFORMATION

#### Toxicity

<b>Aquatic toxicity</b>	Aquatic 48 hour static LC50 value falls within the relatively harmless range of >1000mg/L, according to US Fish and Wildlife documentation. As a screening test for chemical pollutants of natural waters, the Bacterial Multiplication Inhibition Test was performed using Pseudomonas putida.
-------------------------	---

	Due to insolubility of the product, bacteriotoxicity threshold (EC10) of 3363 mg/L was determined on a homogeneous suspension.
<b>Persistence and degradability</b>	Based upon data from similar materials, this product cannot be regarded as readily biodegradable; however, it may be slowly biodegradable
<b>Bioaccumulative potential</b>	No further relevant information available
<b>Mobility in soil</b>	No further relevant information available
<b>Results of PBT and vPvB assessment</b>	
<b>PBT</b>	Not applicable
<b>vPvB</b>	Not applicable
<b>Other adverse effects</b>	No further relevant information available

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

<b>Recommendation</b>	<ul style="list-style-type: none"> <li>➤For SOLID and HOT MOLTEN product that has been cooled and solidified: Land filling in a permitted solid or hazardous waste facility is recommended.</li> <li>➤Handling, transportation, and disposal of material should be conducted in a manner to prevent a nuisance dust hazard.</li> <li>➤Fully containerise the material before handling, and protect from exposure to the outdoors. Ensure there is no restrictions on disposing of bulk or semi-bulk quantities of waste material.</li> </ul> <p style="text-align: right;">(continued on page 10)</p>
-----------------------	---

# SAFETY DATA SHEET


## OleoPrint 155MT Modified Polyol ester of tall oil rosin

### 14. TRANSPORTATION INFORMATION

UN-Number DOT, ADR, DAN, IMDG, IATA	Void
UN proper shipping name DOT, ADR, ADN, IMDG, IATA	Void
Transport hazard class(es) DOT, ADR, ADN, IMDG, IATA	Void
Packaging group DOT, ADR, IMDG, IATA	Void
Environmental hazards: Marine pollutant	No
Special precautions for user	Not applicable
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable
UN "Model Regulation":	-

### 15. REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture	
SARA Section 355 (extremely hazardous substances)	Substance is not listed
Section 313 (Specific toxic chemical listings)	This product does not contain any chemicals subjected to reporting under Section 313 of Title III of the Superfund Amendments and Reauthorization Act and 40CFR372
Section 311 and 312	HC-1 Acute health hazard HC-3 Fire hazard
RCRA	This product is a hazardous waste as listed in 40CFR261.33. It does not exhibit any of the hazardous characteristics listed in 40CFR261, Subpart C

TSCA (Toxic Substances Control Act)	Substance is listed
Proposition 65 Chemicals known to cause cancer	Substance not listed
Chemicals known to cause reproductive toxicity for females	Substance is not listed
Chemicals known to cause reproductive toxicity for males	Substance is not listed
Chemicals known to cause developmental toxicity	Substance is not listed
Carcinogenic categories EPA (Environmental Protection Agency)	Substance is not listed
TLV (Threshold Limit Value established by ACGIH)	Substance is not listed
NIOSH-Ca (National Institute for Occupational Safety and Health)	Substance is not listed
Canadian Domestic Substances List (DSL)	Substance is not listed
GHS label elements	This substance is classified and labelled according to the Global Harmonized System (GHS)
Hazard pictogram	 GHS07
Signal word	Warning
Hazard statements	May form combustible dust concentration in air
<b>PRECAUTIONARY STATEMENTS</b>	
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat / sparks / open flames / hot surfaces – NO SMOKING (continues on page 11)

# SAFETY DATA SHEET

## OleoPrint 155MT Modified Polyol ester of tall oil rosin

### 15. REGULATORY INFORMATION

(Continuation from page 10)

<b>P234</b>	Keep only in original packaging
<b>P243</b>	Take precautionary measures against static discharge
<b>P261</b>	Avoid breathing dust / fume/ gas/mist / vapours/ spray
<b>P262</b>	Do not get in eyes, on skin, or on clothing
<b>P264</b>	Wash thoroughly after handling
<b>P270</b>	Do not eat, drink or smoke when using this product
<b>P280</b>	Wear protective gloves / eye protection
<b>P284</b>	In case of inadequate ventilation wear respiratory protection
<b>P301 + P330 + P331</b>	If swallowed: Rinse mouth. DO NOT induce vomiting
<b>P302 + P352</b>	If on skin: Wash with plenty of soap and water
<b>P304 + P312</b>	IF INHALED: Call a doctor if you feel unwell
<b>P304 + P341</b>	If inhaled: if breathing is difficult, remove person to fresh air and keep comfortable for breathing
<b>P305 + P351 + P338</b>	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do, continue rinsing.

<b>P 301 + P312</b>	If swallowed: call a doctor if you feel unwell
P314	Get medical advice / attention if you feel unwell
P333 + P313	If skin irritation or rash occurs: get medical advice / attention
P363	Wash contaminated clothing before reuse
P402 + P404	Store in a dry place. Store in a closed packaging
P403 + P233	Store in a well ventilated place. Keep packaging tightly closed
P501	Dispose of contents / packaging in accordance with local / regional / national/ international regulations
<b>Chemical safety assessment</b>	A chemical safety assessment has not been carried out

### 16. OTHER INFORMATION

#### DISCLAIMER:

To the best of our knowledge of this substance and on current EC and international regulations, the information contained herein is accurate. However, neither the above-named supplier nor any of its subsidiaries or agents assumes liability whatsoever for the accuracy or completeness of the information contained herein.

<b>Date of preparation:</b>	25 August 2015
<b>Date of previous issue:</b>	10 July 2011
<b>Version:</b>	02
<b>Contact</b>	info@oleo.co.za
Department issuing SDS	Technical Department (Industrial Oleochemical Products (IOP))

# SAFETY DATA SHEET

## OleoPrint 155MT Modified Polyol ester of tall oil rosin

### 15. REGULATORY INFORMATION

(Continuation from page 10)

<b>P243</b>	Take precautionary measures against static discharge
<b>P261</b>	Avoid breathing dust / fume/ gas/mist / vapours/ spray
<b>P262</b>	Do not get in eyes, on skin, or on clothing
<b>P264</b>	Wash thoroughly after handling
<b>P270</b>	Do not eat, drink or smoke when using this product
<b>P280</b>	Wear protective gloves / eye protection
<b>P284</b>	In case of inadequate ventilation wear respiratory protection
<b>P 301 + P312</b>	If swallowed: call a doctor if you feel unwell
<b>P301 + P330 + P331</b>	If swallowed: Rinse mouth. DO NOT induce vomiting
<b>P302 + P352</b>	If on skin: Wash with plenty of soap and water
<b>P304 + P312</b>	IF INHALED: Call a doctor if you feel unwell
<b>P304 + P341</b>	If inhaled: if breathing is difficult, remove person to fresh air and keep comfortable for breathing
<b>P305 + P351 + P338</b>	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do, continue rinsing.

P314	Get medical advice / attention if you feel unwell
P333 + P313	If skin irritation or rash occurs: get medical advice / attention
P363	Wash contaminated clothing before reuse
P402 + P404	Store in a dry place. Store in a closed packaging
P403 + P233	Store in a well ventilated place. Keep packaging tightly closed
P501	Dispose of contents / packaging in accordance with local / regional / national/ international regulations
<b>Chemical safety assessment</b>	A chemical safety assessment has not been carried out

### 16. OTHER INFORMATION

#### DISCLAIMER:

To the best of our knowledge of this substance and on current EC and international regulations, the information contained herein is accurate. However, neither the above-named supplier nor any of its subsidiaries or agents assumes liability whatsoever for the accuracy or completeness of the information contained herein.

<b>Date of preparation:</b>	25 August 2015
<b>Date of previous issue:</b>	10 July 2015
<b>Version:</b>	02
<b>Contact</b>	info@oleo.co.za
Department issuing SDS	Technical Department (Industrial Oleochemical Products (IOP))